

Approved Ropes:

- 1: Ronin HP Rope by Marlow Ropes – 11.5 mm dia.
- 2: Marlow – ProTech 500 – 11.0 mm dia.
- 3: Sterling – Tech 125 – 12.7 mm (½”) dia.
- 4: Yale Cordage – R.I.N.G. – 11.5 mm dia.
- 5: Korda’s – Titania 12 – 12 mm dia.
- 6: Yale Cordage – Scandere – 11.7 mm dia.
- 7: Sterling HTP Red – 13 mm dia.
- 8: Sterling WorkPro – 12.7 mm (½”) dia.
- 9: Edelrid – Performance Static – 12 mm dia.
- 10: Teufelberger – X-Static – 11.7 mm dia.
- 12: Teufelberger – KM III Max – 11 mm & ½” dia.
13. Courant – Rebel – 11 mm dia.
- 14: Pelican Rope – White Rope – 11 mm dia.
- 15: Pelican Rope – 1WPP-160L54-001 – 12.7 mm (½”) dia.
- 16: PMI – RR125BL030M – 12.5 mm dia.
- 17: Sterling – Element – 12.7 mm (½”) dia.
- 18: Yale Cordage – Calamine – 11.7 mm dia.
19. Sterling – Scion – 11.5 mm dia.
20. PMI – E-Z Bend – 11 mm dia.
- 21: Yale Cordage – XTC-16 – 13 mm dia.
22. Teufelberger – Platinum Protect PES/PA – 11 mm dia